§ 60.2880

[Date to be specified in state plan] a

For the air pollutant	You must meet this emission limitation ^b	Using this averaging time	And determining compliance using this method
Hydrogen chloride	300 parts per million dry volume	3-run average (For Method 26, collect a minimum volume of 120 liters per run. For Method 26A, collect a minimum volume of 1 dry standard cubic meter per run).	Performance test (Method 26 or 26A at 40 CFR part 60, appendix A–8).
Lead	2.1 milligrams per dry standard cubic meter.	3-run average (collect a min- imum volume of 1 dry stand- ard cubic meters).	Performance test (Method 29 at 40 CFR part 60, appendix A– 8). Use ICPMS for the analytical finish.
Mercury	0.0053 milligrams per dry stand- ard cubic meter.	3-run average (For Method 29 and ASTM D6784-02 (Reapproved 2008), collect a minimum volume of 2 dry standard cubic meters per run. For Method 30B, collect a minimum sample as specified in Method 30B at 40 CFR part 60, appendix A).	Performance test (Method 29 or 30B at 40 CFR part 60, appendix A–8) or ASTM D6784–02 (Reapproved 2008). c
Oxides of nitrogen	190 parts per million dry volume	3-run average (for Method 7E, 1 hour minimum sample time per run).	Performance test (Method 7 or 7E at 40 CFR part 60, appendix A-4).
Particulate matter (filterable)	270 milligrams per dry standard cubic meter.	3-run average (collect a min- imum volume of 1 dry stand- ard cubic meters).	Performance test (Method 5 or 29 at 40 CFR part 60, appen- dix A-3 or appendix A-8).
Sulfur dioxide	150 parts per million dry volume	3-run average (for Method 6, collect a minimum of 20 liters per run; for Method 6C, 1 hour minimum sample time per run).	Performance test (Method 6 or 6c at 40 CFR part 60, appendix A-4).

^a The date specified in the state plan can be no later than 3 years after the effective date of approval of a revised state plan or

[78 FR 9210, Feb. 7, 2013]

Subpart EEEE—Standards of Performance for Other Solid Waste Incineration Units for Which Construction is Commenced After December 9, 2004, or for Which Modification or Reconstruction is Commenced on or After June 16, 2006

SOURCE: 70 FR 74892, Dec. 16, 2005, unless otherwise noted.

INTRODUCTION

§ 60.2880 What does this subpart do?

This subpart establishes new source performance standards for other solid waste incineration (OSWI) units. Other solid waste incineration units are very small municipal waste combustion units and institutional waste incineration units.

§60.2881 When does this subpart become effective?

This subpart takes effect June 16, 2006. Some of the requirements in this subpart apply to planning the incineration unit and must be completed even before construction is initiated on the unit (i.e., the preconstruction requirements in §§60.2894 and 60.2895). Other requirements such as the emission limitations and operating limits apply when the unit begins operation.

APPLICABILITY

§ 60.2885 Does this subpart apply to my incineration unit?

Yes, if your incineration unit meets all the requirements specified in paragraphs (a) through (c) of this section.

- (a) Your incineration unit is a new incineration unit as defined in §60.2886.
- (b) Your incineration unit is an OSWI unit as defined in §60.2977 or an air curtain incinerator subject to this subpart

February 7, 2018.

^b All emission limitations (except for opacity) are measured at 7 percent oxygen, dry basis at standard conditions. For dioxins/furans, you must meet either the total mass basis limit or the toxic equivalency basis limit.

^c Incorporated by reference, see § 60.17.

Environmental Protection Agency

as described in §60.2888(b). Other solid waste incineration units are very small municipal waste combustion units and institutional waste incineration units as defined in §60.2977.

(c) Your incineration unit is not excluded under §60.2887.

§ 60.2886 What is a new incineration unit?

- (a) A new incineration unit is an incineration unit subject to this subpart that meets either of the two criteria specified in paragraphs (a)(1) or (2) of this section.
- (1) Commenced construction after December 9, 2004.
- (2) Commenced reconstruction or modification on or after June 16, 2006.
- (b) This subpart does not affect your incineration unit if you make physical or operational changes to your incineration unit primarily to comply with the emission guidelines in subpart FFFF of this part. Such changes do not qualify as reconstruction or modification under this subpart.

§ 60.2887 What combustion units are excluded from this subpart?

This subpart excludes the types of units described in paragraphs (a) through (q) of this section, as long as you meet the requirements of this section.

- (a) Cement kilns. Your unit is excluded if it is regulated under subpart LLL of part 63 of this chapter (National Emission Standards for Hazardous Air Pollutants from the Portland Cement Manufacturing Industry).
- (b) Co-fired combustors. Your unit, that would otherwise be considered a very small municipal waste combustion unit, is excluded if it meets the five requirements specified in paragraphs (b)(1) through (5) of this section.
- (1) The unit has a Federally enforceable permit limiting the combustion of municipal solid waste to 30 percent of the total fuel input by weight.
- (2) You notify the Administrator that the unit qualifies for the exclusion.
- (3) You provide the Administrator with a copy of the Federally enforceable permit.
- (4) You record the weights, each calendar quarter, of municipal solid waste and of all other fuels combusted.

- (5) You keep each report for 5 years. These records must be kept on site for at least 2 years. You may keep the records off site for the remaining 3 years.
- (c) Cogeneration facilities. Your unit is excluded if it meets the three requirements specified in paragraphs (c)(1) through (3) of this section.
- (1) The unit qualifies as a cogeneration facility under section 3(18)(B) of the Federal Power Act (16 U.S.C. 796(18)(B)).
- (2) The unit burns homogeneous waste (not including refuse-derived fuel) to produce electricity and steam or other forms of energy used for industrial, commercial, heating, or cooling purposes.
- (3) You notify the Administrator that the unit meets all of these criteria.
- (d) Commercial and industrial solid waste incineration units. Your unit is excluded if it is regulated under subparts CCCC or DDDD of this part and is required to meet the emission limitations established in those subparts.
- (e) Hazardous waste combustion units. Your unit is excluded if it meets either of the two criteria specified in paragraph (e)(1) or (2) of this section.
- (1) You are required to get a permit for your unit under section 3005 of the Solid Waste Disposal Act.
- (2) Your unit is regulated under 40 CFR part 63, subpart EEE (National Emission Standards for Hazardous Air Pollutants from Hazardous Waste Combustors).
- (f) Hospital/medical/infectious waste incinerators. Your unit is excluded if it is regulated under subparts Ce or Ec of this part (New Source Performance Standards and Emission Guidelines for Hospital/Medical/Infectious Waste Incinerators).
- (g) Incinerators and air curtain incinerators in isolated areas of Alaska. Your incineration unit is excluded if it is used at a solid waste disposal site in Alaska that is classified as a Class II or Class III municipal solid waste landfill, as defined in §60.2977.
- (h) Rural institutional waste incinerators. Your incineration unit is excluded if it is an institutional waste incineration unit, as defined in §60.2977, and the application for exclusion described in paragraphs (h)(1) and (2) of